


# SANYO Cadnica


## Cell Type KR-600AAL Specifications




Nominal Capacity		600mAh	
Nominal Voltage		1.2V	
Charging Current	Standard	60mA	
	Quick	120mA	
Charging Time	Standard	14 to 16Hrs.	
	Quick	7 to 8Hrs.	
Ambient Temperature	Charge	Standard	0°C to +45°C [ +32°F to 113°F ]
		Quick	0°C to +45°C [ +32°F to 113°F ]
	Discharge	-20°C to +60°C [ -4°F to 140°F ]	
	Storage	-30°C to +50°C [ -22°F to 122°F ]	
Internal Impedance (Av.) (at 50% discharge)		24.0mΩ (at 1000Hz)	
Weight		19g/ 0.67oz	
Dimensions(D)x(H) (with tube)		14.3 <sup>0</sup> <sub>-0.5</sub> × 48.9 <sup>0</sup> <sub>-1</sub>	mm
		0.56 <sup>0</sup> <sub>-0.02</sub> × 1.93 <sup>0</sup> <sub>-0.04</sub>	inch

### Typical Characteristics


#### Charge




#### Discharge(at high rate)




#### Charge



#### Discharge(at high rate)



#### Discharge(at low rate)



#### Temperature(Charge & Discharge)

