

Specification of Manganese Batteries

type : UM-5

Issued : 01. Apr. 1999

SANYO Electric Co., Ltd.
Soft Energy Business Headquarters
Overseas Sales Dept.
(TEL : ++81-6-6900-3775)
(FAX : ++81-6-6901-7797)

1. Scope : This specification is applicable to the following Dry Batteries Supplied to SANYO Energy (Europe) Corporate GmbH from SANYO Electric Co., Ltd.

- 2. Type : UM-5
- 3. Nominal Voltage : 1.5V
- 4. Figure and Dimensions : See Fig. 1
- 5. Standard Weight : 7g
- 6. Terminals : + : Cap Terminal, - : Base Terminal
- 7. Quality Characteristics

7.1 Dimensions : Dimensions are shown in Fig. 1.

7.2 Terminal : There shall be no rust or deformation that occurs troubles practically.

7.3 Appearance : There shall be no rust, deformation or scratch that occurs troubles practically.

7.4 Electrical Characteristics

(Table 1)

Item		Requirement		Test Conditions
Open-Circuit Voltage (V)		Initial	1.52 - 1.72	Temp. : 20 +/- 2 centigrade RH : 65 +/- 20%
		After 2 years	1.50 - 1.72	
Service Life (H)	Discharge at 15 ohm	Initial	Over 3.0	Temp. : 20 +/- 2 centigrade RH : 65 +/- 20% End Voltage : 0.85V Daily period : 10min
		After 2 years	Over 2.0	

8. Test

8.1 Storage and Test Conditions

(1) Storage Condition

Unless otherwise specified, storage condition shall be kept at 20 +/- 2 centigrade and at 65 +/- 20%RH.

(2) Test Condition

Unless otherwise specified, test shall be conducted at 20 +/- 15 centigrade and at 65 +/- 20%RH.

8.2 Instruments and Devices

(1) Voltmeters

The voltmeters shall be of Class 0.5 or better specified in JIS C1102 (Electrical Indicating Instruments) and shall have a internal resistance not less than 1,000 ohm/V. But voltmeters for service life test shall have a internal resistance not less than 1,000 ohm/V or not less than 10 times of load resistance, which ever is larger.

(2) Load Resistance

The load resistance shall include all resistances in external circuit, and its tolerance shall be +/-